



MATERIAL SAFETY DATA SHEET
HOLDIT T62

Revised Date: June 2011

Page 1 of 4

MODIFIED by HOLDIT

SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: HOLDIT T62
Other Names: T62 Studlock
Use: High Strength Threadlocker
Part Number: T62-10 (10ml), T62-50 (50ml), T62-250(250ml)
Supplier: HOLDIT Pty Ltd
Address: 21 Heath Street
Lonsdale, South Australia, 5160
Emergency Tel: +61 1300 552 680
Telephone: +61 8 8186 0844
Fax: +61 8 8186 0252

Emergency Contact
Address: See Above Address

Other Information: The information below is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This Company shall not be held liable for any damage resulting from handling or from contact with the above product.

SECTION 2. HAZARDOUS IDENTIFICATION

Classified as hazardous according to criteria of NOHSC.

Hazard Category: Irritant
Risk Phrases: R36/38 Irritating to eyes, respiratory system and skin.
R43 May cause sensitization by skin contact
Safety Phrases: S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S27 Take off immediately all contaminated clothing.
S28 After contact with skin, wash immediately with plenty of water
S3/14 keep in a cool place.
S3/9/14 Keep in a cool, well ventilated place away from direct sunlight
S37 Wear suitable gloves
S37/39 Wear suitable gloves and eye/face protection
S39 Wear eye/face protection
S7 Keep container tightly closed
S9 Keep container in a well ventilated place



MATERIAL SAFETY DATA SHEET HOLDIT T62

Revised Date: June 2011

Page 2 of 4

MODIFIED by HOLDIT

SECTION 3. COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Name	CAS No.	Percent %.	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
Poly Glycol Dimethacrylate	NDA-09-0104	25852-47-5	35-45	n.e	n.e
Polyethylene Glycol Ester	NDA-09-0311	27813-02-1	25-35	n.e	n.e
Polyester Resin	NDA-09-0120	Proprietary	20-30	n.e	n.e
Saccharin	NDA-09-0150	81-07-2	2-5	n.e	n.e
Cumene Hydroperoxide	NDA-09-0101	80-15-9	0.5-2.4	n.e	n.e

SECTION 4. FIRST AID MEASURES

Eye Contact:	<i>A primary route of exposure that will cause eye irritation on contact.</i>
FIRST AID:	Flush eyes with generous amounts of water for 20-30 minutes, lifting both upper and lower eyelids occasionally. Get medical attention.
Skin Contact:	<i>A primary route of exposure that may cause moderate skin irritation and allergic skin reaction. May cause rash, redness, swelling and blistering (symptoms may be delayed).</i>
FIRST AID:	Thoroughly wash exposed area with soap and water. If irritation develops, seek medical attention. Launder clothing before reuse.
Inhalation:	<i>As supplied; not a significant hazard. However vapours generated at elevated temperatures, may cause respiratory tract irritation. Symptoms may include coughing, mucous production and shortness of breath.</i>
FIRST AID:	If overcome by exposure, victim should be removed to fresh air immediately. Give artificial respiration as needed. Get immediate medical attention.
Ingestion:	<i>Ingestion may cause irritation of the gastrointestinal tract and depression of the central nervous system leading to loss of consciousness.</i>
FIRST AID:	Do not induce vomiting. Immediately seek medical attention.
Chronic Effects:	Material or its emissions may defat skin, cause contact dermatitis and thereby aggravate existing skin or systemic diseases.

SECTION 5. FIRE FIGHTING MEASURES

Flash Point: 93°C	PMCC	Auto Ignition Temperature:	Not determined.
Flammability limits % in Air:	LEL: not determined	UEL:	Not determined.
Extinguishing Media:	Use carbon dioxide, foam, dry chemical and/or water spray.		
Special Firefighting:	Wear a NOISH approved self-contained breathing apparatus operated in pressure-demand or other positive pressure when fighting fires. Sealed containers may rupture explosively if exposed to heat.		
Unusual Fire Hazards & Conditions to avoid:	Combustion of product may produce oxides of carbon.		
RECOMMENDED NFA/HMIS RATING			
Health 2	Flammability 1	Reactivity 2	Personal Protection
<i>Note: ratings may differ according to application, environment, and physical state.</i>			



MATERIAL SAFETY DATA SHEET HOLDIT T62

Revised Date: June 2011

Page 3 of 4

MODIFIED by HOLDIT

SECTION 6. ACCIDENTIAL RELEASE MEASURES

Steps to be taken if material is spilled or released: Absorb material on inert filler, vermiculite, floor absorb or other absorbent material. Transfer to ventilated area and dispose of properly.

Waste Disposal Methods: Dispose of material in accordance with local, state and federal regulations.

Safe Handling & Storage: Avoid prolonged skin contact. Store product in a cool dry place.

Other precautions and special hazardous Information: This material contains inhibitors which upon depletion can result in an excessive thermal reaction.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Refer to Section 8 of this MSDS.

Conditions for safe storage, including any incompatibilities

Keep only in the original container in a cool, well ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: Not necessary with normal use.

Protective Gloves: Use vinyl or rubber gloves.

Eye Protection: Wear NIOSH approved safety goggles.

Ventilation used: Standard Exhaust.

Protective Clothing &

Equipment: Wear impervious clothing to prevent repeated, prolonged skin contact.

Hygienic Work Practices: Practice good hygiene, and wash hands after using this product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: >198°C

Vapour Density: n.e Air=1

VOC: 0.093

Vapour Pressure: n.e

Density of Coating:

Melting Point: n.a

Specific Gravity: >1.0 Water=1

Evaporation Rate: n.a

Water Reactive: no

Solubility in Water: Insoluble

Appearance: Red Translucent liquid **Odour:** Cumene Odour.

SECTION 10. STABILITY AND REACTIVITY

Stability: **Stable:** x **Unstable:**

Hazardous Polymerization: **May occur:** **will not occur:** x

Conditions to avoid: None.

Incompatibility: Avoid strong oxidizing agents and storage temperatures exceeding 48°C. avoid exposure to steel or rust.

Hazardous Decomposition Products: Combustion yields oxides of carbon and possible toxic fumes.



MATERIAL SAFETY DATA SHEET
HOLDIT T62

Revised Date: June 2011

Page 4 of 4

MODIFIED by HOLDIT

SECTION 11. TOXICOLOGY INFORMATION

Component	ORAL LD50	DERMAL LD50	INHALATION LC50
Poly Glycol Dimethacrylate	Not Determined	Not Determined	Not Determined
Polyethylene Glycol Ester	5000mg/Kg (Rat)	Not Determined	Not Determined
Polyester Resin	Not Determined	Not Determined	Not Determined
Saccharin	Not Determined	Not Determined	Not Determined
Cumene Hydroperoxide	800-1600mg/Kg (Rat)	130-1500mg.Kg(Rat)	220 ppm (Rat)

SECTION 12. ECOLOGICAL INFORMATION

This product can be harmful to aquatic organisms. Do not allow to contaminate waterways or soil.

SECTION 13. DISPOSAL CONSIDERATIONS

General Information Local and National regulations. This material and its container must be disposed of in a safe way.

SECTION 14. TRANSPORT INFORMATION

ADR/RID	The product is not classified as dangerous for carriage.
IMDG	The product is not classified as dangerous for carriage.
IATA	The product is not classified as dangerous for carriage.

SECTION 15. REGULATORY INFORMATION

None Allocated

SECTION 16. OTHER INFORMATION

Detaching this notification from the Material Safety Data Sheet is prohibited by law and any copying or distribution of same requires this attachment be included.

This products contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act 1986 and 40 CFR 372:

CAS#	CHEMICAL NAME	% BY WEIGHT
80-15-9	Cumene Hydroperoxide	2.25
107-21-1	Ethylene Glycol	0.21

This product contains the following materials that under California Proposition 65 of the Safe Drinking Water and Toxic Enforcement Act of 1986 are recognized to cause cancer or reproductive toxicity.

Material	CAS #	Concentration %	Cancer Agent	Reproductive Toxin
None				

CONTACT POINT

Technical Contact

Number: Head Office Tel: 1300 552 680

End of MSDS