



# Technical Datasheet Gasket Remover 49673

Revised Date: June 2011

## Description

Dynatex Gasket Remover is an aerosol product designed to remove gasket residue from any type of metal or plastic housing. Dynatex Gasket Remover quickly removes baked-on gaskets, silicone weatherstrip adhesive, carbon deposits, dried oil, adhesives, grease and paint. Removes gaskets in 10-12 minutes. Prepares metal parts for new gasket installation.

- Penetrates and cleans intricate shapes
- Eliminates excessive scraping and potential damage to flanged surfaces
- Saves time and labour

## Applications

Dynatex Gasket Remover Removes

- Baked-on gaskets and gasket cements
- Gaskets from small, difficult to reach areas
- Formed-in-place gaskets
- Gaskets from aluminium without scraping

## Instructions for Use

1. Provide adequate ventilation.
2. Protect painted and non-metal surfaces from overspray. The product will remove paint.
3. Shake can well. For best results, the aerosol should be at room temperature before spraying.
4. Holding can 8 to 10 inches from surface to be coated, press nozzle and discharge the product onto the affected areas.
5. Allow to set for at least 15 minutes. Remove dissolved gasket with a plastic scraper and rags. Repeat if necessary.

## Storage

Dynatex Gasket Remover should ideally be stored in a cool, dry location in unopened containers at a temperature between 4°C to 24°C unless otherwise labelled. DO NOT store with 1 meter of roofline of the warehouse of storage building. Store in accordance with NFPA 30B for level 3 aerosol. Dynatex Gasket Remover has a shelf life of 18 months from date of shipment.

## Performance of Cured Material

Physical State	Liquid
Colour/Appearance	Clear Liquid
Odour	Ether-Like
Specific Gravity	1.22
Boiling/Cond. Point	37°C
Solubility	Soluble in water
pH	Not Applicable
Evaporation Rate	>1 (BuAc=1)
VOC%	24%
Vapour Pressure	Not Applicable
NFPA Flammability Rating	4*
* Highly Flammable	

## Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$   
 $\text{N/mm} \times 5.71 = \text{lb/in}$   
 $\text{MPa} \times 145 = \text{psi}$   
 $\text{N/mm}^2 \times 145 = \text{psi}$   
 $\text{N} \times 0.225 = \text{lb}$   
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$   
 $\text{N}\cdot\text{mm} \times 0.738 = \text{lb}\cdot\text{ft}$   
 $\text{mPa}\cdot\text{s} = \text{cP}$

## Presentation

Available in a 369g can.

## Health & Safety in Use

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**